





| Framework | • Reinforced Cement Concrete | Painting | Plastic emulsion with NCL Altek |
|-----------------|--|------------------------------|--|
| Super Structure | Table Molded Bricks in cement mortar Outside walls 9 inch thick Internal walls 4 ½ inch thick | | Cement paint on external facade Front elevation with RENOVO texture paint |
| Doors | Main door with teakwood frames and shutters Designer internal flush doors with teakwood frames Top quality fittings on all doors | Kitchen | Granite platform with steel sink 2 feet height Dado with tiles above the counter Provision for exhaust fan and suitable Electrical points for Kitchen appliances |
| Windows | •UPVC Window systems | Generator / Back-up Power | • All Lights and Fans points of the Flats and Corridor shall be operating with the Generator during power failure (Capacity of Generator will depend on the number of Apartments) |
| Electrical | Concealed copper wiring with adequate points for TV, Exhaust Fans, Geyser, AC, etc MCB will be provided in all Flats | | |
| | Standby generator shall be providedWiring Make: PolycabSwitches Make: Legrand | Elevators | Elevators of 6 or 8 Passengers Capacity as planned with standby Generator Lift Make: Johnson Lifts |
| Flooring | Vitrified Tiles: Johnson / Euro Tiles or equivalent make | Telephone & Television | Telephone points and Cable TV point shall be provided in Living and all bedrooms |
| Sanitary | Colored Ceramic tiles up to 7 feet height Concealed Pipeline Ivory colored Washbasin Colored Indian or European commode matching with tiles | Water Supply | 24 hours of Water Supply from Borewell, in addition to municipal water supply with the help of storage tanks of suitable capacity Water Softener shall be provided to reduce the hardness of the borewell water |
| | Standard fittings and provision for Geyser in Toilets Tiles Make: Johnson Tiles or Equivalent Brand Basins Make: Parryware / Cera or Equivalent Brand Standard Fittings: Jaquar | Common Areas | Corridor and Staircase are also with Granite flooring Corridor is provided with False Ceiling and up to 8 inch height Tile Cladding for Corridor walls |
| Plastering | • Smooth finish to internal walls • Sponge finish to external walls | Security System | Door Video Cameras are provided for Security Purpose |