



SPECIFICATIONS___

| Framework | Reinforced Cement Concrete | Plastering | ■ Smooth finish to internal walls |
|-----------------|---|---|---|
| Super Structure | ■ Fly ash Bricks | Painting | Sponge finish to external walls |
| | Outside walls 9 inch thick | | Plastic emulsion with NCL Altek or Luppam |
| | Internal walls 4.5 inch thick | | on Internal walls Cement paint on external facade |
| Doors | Main door with teakwood frames and shutters Designer internal flush doors with teak wood frames | Kitchen | Front elevation with RENOVO texture paint |
| | | | Granite platform with steel sink |
| | Top quality fittings on all doors | | 2 feet height Dado with tiles above the counter |
| Windows | ■ UPVC Window systems | | Provision for exhaust fan and suitable electrical points for kitchen appliances |
| Electrical | Concealed copper wiring with adequate points for TV, Exhaust Fans, Geyser, AC, etc MCB will be provided in all Apartments Standby generator shall be provided | Generator / Back-up Power | All lights and fans points of the Apartments and Corridor shall be operating with the Generator during power failure except plug points like AC, Refrigerator, etc. (Capacity of Generator will depend on the number of Apartments) |
| | Wiring Make: Polycab / Equivalent Brand Switches Make: Legrand / Equivalent Brand | | |
| Flooring | Vitrified Tiles 800/800 mm in Living and DiningWooden Flooring in all Bedrooms | Elevators | Elevators of 6 or 8 passengers capacity as planned with standby Generator Lift Make: Johnson / Equivalent |
| Sanitary | Colored Ceramic tiles up to 7 feet heightConcealed PipelineIvory colored Washbasin | Telephone & Television Water Supply Common Areas | ■ Telephone points and Cable TV point shall be provided in Living and all bedrooms |
| | Colored Indian or European commode matching with tiles Standard fittings and provision for Geyser | | 24 hours of water supply from Borewell, in addition to municipal water supply with the help of storage tanks of suitable capacity Water Softener shall be provided to reduce the hardness of the bore water |
| | in Toilets | | |
| | Bathtub will be provided in the master bedroom toilet as planned | | Corridor & Staircase are also with Granite flooring |
| | Tiles Make: Johnson Tiles or Equivalent Brand Basins Make: Parryware / Cera / Roca or Equivalent Brand | | Corridor is provided with False CeilingUp to 8" height Tile Cladding for Corridor walls |
| | Standard Fittings: Jaquar / Kohler or Equivalent Brand | Security System | Door Video Cameras are provided for Security Purpose |